

GENERAL NOTES:

- A. REFER TO PROJECT MANUAL FOR ADDITIONAL REQUIREMENTS
- B. ALL SITE DIMENSIONS TO THE GUTTER LINE OF CURB, CONCRETE OR PROPERTY LINE UNLESS OTHERWISE NOTED. CONTRACTOR TO FIELD VERIFY EXISTING CONDITIONS BY DETAILED INSPECTION
- C. COORDINATE WORK WITH OTHER SITE RELATED DEVELOPMENT DRAWINGS.
- D. REFER TO STRUCTURAL PLANS FOR DEVELOPMENT OF SIDEWALKS ADJACENT TO FOUNDATIONS.
- E. PRIOR TO INSTALLATION, GENERAL CONTRACTOR TO CONFIRM THAT LIGHT POLES, LANDSCAPING AND UTILITIES DO NOT CONFLICT WITH SIGN LOCATION SHOWN. IF ANY POTENTIAL CONFLICT IS DISCOVERED, GENERAL CONTRACTOR TO CONTACT THE O'REILLY PROJECT ADMINISTRATOR BEFORE PROCEEDING.

KEY NOTES:

- CONCRETE PAVING: REFER TO DETAIL 1/C3.
- ALTERNATE #1: ASPHALT PAVING REFER TO DETAIL 2/C3. REFER TO PROJECT MANUAL.
- 2 CONCRETE PAVING: REFER TO DETAIL 1/C3.
- (3) CONCRETE CURB: REFER TO DETAIL 3/C3.
- (4) CONCRETE SIDEWALK: REFER TO DETAIL 4/C3.
- 5 CONCRETE DOOR LANDING:
- REFER TO DETAIL 4/C3 AND STRUCTURAL DETAILS. RAMP PAVING AS INDICATED. LANDING CAN BE POURED MONOLITHIC IF CONCRETE PAVING IS USED.
- 6 STEEL BOLLARD: REFER TO DETAIL 6/C3. PROVIDE (2) AT TRASH PAD, GAS METER. AND OVERHEAD DOOR, PROVIDE (9) AT SIDEWALK. REFER TO STRUCTURAL PLAN FOR LOCATION.
- 7 HANDICAP PARKING SIGN: REFER TO DETAIL 7/C3.
- 8 CONCRETE HANDICAP RAMP: REFER TO DETAIL 9/C3.
- 9 HANDICAP PARKING SYMBOL:
- REFER TO DETAIL 5/C3.
- 10 HANDICAP ACCESS UNLOADING ZONE: SLOPE 2% MAX. EACH WAY (ADA COMPLIANT) AND STRIPE AS SHOWN.
- SCREEN FENCE: REFER TO DETAIL 12/C3.
- SCREEN FENCE GATES: REFER TO DETAIL 11/C3.
- (13) CONCRETE BUMPER BLOCKS: 8"w x 5"h x 6'-0" LONG CONCRETE. ANCHOR TO PAVING WITH (2) 1'-6" LONG #4 REBAR (TO SIT LEVEL WITH PAVING).
- PARKING LOT LIGHTING:
 REFER TO SITE UTILITIES PLAN FOR LOCATION AND TYPE. (15) LIMITS OF NEW PAVING:
- MATCH EXISTING PER CITY AND OR STATE STANDARDS.
- (16) ROLL DOWN CURB: TERMINATE AND ROLL DOWN NEW CURB WHERE INDICATED. ROLL DOWN AT 1:2.
- (17) CONCRETE CURB:
- NEW CONCRETE CURB TO MATCH EXISTING ADJACENT CURB.
- PROVIDE 4" WIDE PARKING LOT STRIPING AS SHOWN. USE HIGHWAY MARKING PAINT - YELLOW (2 COATS)
- (19) NOT USED
- SIGN LOCATION:
- SIGN FURNISHED AND INSTALLED BY OWNER. REFER TO SITE UTILITIES PLAN FOR DETAILS.
- CONCRETE DRIVE APRON: TO BE INSTALLED PER CITY AND OR STATE DESIGN STANDARDS. IF NO STANDARDS PROVIDE CONCRETE PAVING CONSTRUCTION AS SHOWN ON DETAIL 1/C3.
- (22) CONCRETE HANDICAP RAMP: REFER TO DETAIL 8/C3.
- 23 LOADING ZONE: PROVIDE 4" WIDE PARKING LOT STRIPING AS SHOWN. USE HIGHWAY MARKING PAINT - YELLOW (2 COATS)
- BICYCLE PARKING: EQUAL TO COLUMBIA CASCADE 2170-3-C. POWDER COATED COLOR TO BE EVERGREEN. INSTALL USING THE PEDESTAL MOUNT PER MANUFACTURER'S REQUIREMENTS. (REFER TO DETAIL 2/C2)
- HEAVY DUTY CONCRETE OR ASPHALT PAVING PER CITY STANDARDS AS INDICATED BY ().
- (26) 6'-0" TALL MASONRY SCREEN FENCE. REFER TO DETAIL STRUCTURAL.

UNDBER(

HOMA

COMM # 3484

DATE: 9-27-13 REVISION

DATE: 4-23-14 5-5-15